

1.8M C & Ku-Band High Wind Antenna

Series 2194

Technical Specifications

Electrical		Series 2194 C-Band	Series 2194 Ku-Band
Antenna Size		1.8 M (71 in.)	1.8 M (71 in.)
Operating Frequency (GHz)	Receive	3.625 - 4.20 GHz	10.95 - 12.75 GHz
	Transmit	5.85 - 6.425 GHz	13.75 - 14.50 GHz
Midband Gain (+/- .2 dB)	Receive	35.50 dBi	45.20 dBi
	Transmit	39.50 dBi	46.70 dBi
Polarization		Circular or Linear	Linear
Feed Interface	Receive	WR229	WR75
	Transmit	Type N or WR137	
Cross-Polarization		-30 dB within B.P.E. (linear) 15.5 dB Rx, 17.7 dB Tx (circular)	-30 dB on axis
Axial Ratio		1.3 VAR (2.28 dB) Tx, 1.4 VAR (2.95 dB) Rx	N/A
VSWR		1.3:1 Max.	1.3:1 Max. Tx, 1.5:1 Max. Rx

Mechanical	
Reflector Material	Glass Fiber Reinforced Polyester SMC
Antenna Optics	Prime Focus, Offset Feed
Mast Pipe Size	6" SCH 40 Pipe (6.62" OD) 16.83 cm.
Elevation Adjustment Range	15° to 80°, Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous Coarse Adjust, ±10° Fine Adjustment

Environmental Performance		
Wind Loading	Operational	65mph (104km/h) with 0.5 dB loss @ 14.25 GHz 75mph (120km/h) with 1.0 dB loss @ 14.25 GHz 75mph (120km/h) with 0.5 dB loss @ 6.14 GHz 90mph (145km/h) with 1.0 dB loss @ 6.14 GHz
	Survival	150mph (240km/h)
Temperature	Operational	-40° to 140° F (-40° to 60° C)
	Survival	-50° to 160° F (-46° to 71° C)
Rain	Operational	1/2"/hr
	Survival	2"/hr
Ice	Operational	-----
	Survival	1/2" radial
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Solar Radiation		360 BTU/h/ft2

GENERAL DYNAMICS SATCOM Technologies

1500 Prodelin Drive • Newton, NC 28658 USA • Telephone: +1-828-464-4141 • Fax: +1-828-464-4147
Email: vsat@gdsatcom.com • Web Site: www.gdsatcom.com

1000-043 Rev. 6/14