

Small Deep-Space Transponder (SDST)

Reliable X-Band and Ka-Band Deep Space Transmission



Currently flying on multiple deep space missions totaling > 1,000,000 in-flight operational hours:

Deep Space-1, Mars Odyssey, Spitzer Space Telescope, Mars Rovers: Spirit, Opportunity, Curiosity, Deep Impact, Messenger, STEREO, Mars Reconnaissance Orbiter, Phoenix, Dawn, Kepler, Juno and MAVEN

NASA's Deep Space Network (DSN) compatible

Radiation and SEU Tolerant

MIL-STD-1553 Interfaces – Standard and Low Power

Option for Ka-Band downlink (independent of X-band Functionality)

The Small Deep Space Transponder (SDST), developed by General Dynamics and NASA's Jet Propulsion Laboratory, is a spacecraft terminal for X-Band and Ka-Band telecommunications with the NASA Deep Space Network. Making extensive use of MMICs, multi-chip modules, and a new signal processing ASIC, the SDST's flexible design provides the capability to meet the telecommunication needs of nearly every deepspace mission.

The SDST has two configurations. The X/X configuration consists of an X-band receiver and an X-band 880F1 exciter. The X/X/Ka configuration consists of an X-band receiver, an X-band 880F1 exciter and an X-band 840F1 exciter. The 840F1 exciter drives an external x4, X-to-Ka-band multiplier mounted to the user's Ka-band power amplifier, allowing interconnection by coaxial cable rather than waveguide.

Small Deep-Space Transponder (SDST)

Features

- Deep-Space Network Compatible
- Redundant I/O for Cross-Strapping
- X-Band Receiver, X and Ka-Band Exciters
- 2.1 dB Typical Noise Figure @25°C
- -158 dBm Typical Sensitivity @ 25°C
- Temp Compensated Receiver VCO
- Low Exciter Spurious, Phase Noise, and Allan Deviation
- Radio Science Mode (using USO Input)
- 6 ns Typical Ranging Delay Variation
- 30 Mbps Max TLM Symbol Rate
- 0.5 ns Typical Carrier Delay Variation
- MIL-STD-1553 Interface – Standard and Low Power
- External Power Converter Synchronization Capability
- Operates Under Launch Environments
- Radiation and SEU Resistant
- Internal Telemetry Modulation Encoder
- Internal Command Detector with External Baseband Input
- Mounting in Either of Two Axes
- Firmware Options:
 - Carrier Tracking Loop Bandwidth
 - Command Detector Subcarrier Frequencies and Data Rates
 - Custom Command/Telemetry Interface Format

Transponder

- X-Band UL Freq Range (Fixed Channel): 7.145 - 7.235 GHz
- X-Band DL Freq Range (Fixed Channel): 8.400 - 8.500 GHz
- X-Band TX/RX Ratio: 880/749
- Ka-Band DL Freq Range (Fixed Channel): 31.800 - 32.300 GHz
- Ka-Band TX/X-Band RX Ratio: 3360/749
- Carrier Delay Variation: < 3 ns p-p
- Ranging Delay Variation: < 15 ns p-p

X-Band Receiver

- Noise Figure: < 2.5 dB @25°C; < 3.2 dB over temp, aging, radiation
- Carrier Tracking Signal Range: -70 to -158 dBm (to -60 dBm nom)
- Carrier Loop Threshold BW (2-sided): 20 Hz or 50 Hz (others avail)
- Carrier Loop Damping Factor: 0.5 @ 0 dB loop S/N (Type 1, second order loop)
- Tracking Range: ±200 kHz minimum
- Command Subcarrier Frequency: 16 kHz
- Command Subcarrier/Tone Mod Index: 0.5 - 1.5 radians peak
- Command Data Rates: 7.8125 - 4000 bps (2n steps, PM/PSK, NRZ)
- Ranging Uplink Carrier Suppression: 0 to 5 dB (sine wave)
- Ranging Filter Type: 15th order finite impulse response filter
- Ranging Filter 3 dB BW: 1500 kHz nom (other options available)
- Temperature Stability: ±3 ppm (-20 to +60°C)

Exciters (Independent X- and Ka-Band)

- X-Band 880F1 Output Power: +13 dBm +2.5 dB, -1.5 dB
- X-Band 840F1 Output Power (to ext X4 Mult): +23.5 dBm ±2.5 dB
- X4 Multiplier Input Power: +18 dBm +3 dB, -0 dB
- X4 Multiplier Output Power (3360F1): -1 dBm minimum
- X-Band Phase Noise, Aux Osc Mode (add 12 dB for Ka-Band):
 - -20 dBc/Hz (1 Hz offset) maximum
 - -75 dBc/Hz (100 Hz - 100kHz offset) maximum
- Frequency Stability, 0 to 50°C: ± 5.0 ppm maximum
- X-Band Spurious & Harmonic Outputs: < -50 dBc
- Phase Modulator Linearity: < 10% variation from straight-line to 2.5 radians pk
- TLM Modulation Modes: Subcarrier, BPSK (to 15 Mbps), QPSK (to 30 Mbps) upgradeable to 100 Mbps

- TLM Encoding: Convolutional 15-1/2, 15-1/4, 15-1/6, 7-1/2; Manchester and Bypass (custom available)
- TLM Subcarrier: 2 kHz to 18 MHz square or sine wave
- TLM Phase Deviation: 0° to 135° peak minimum
- Ranging Modulation Index: 4.375, 8.75, 17.5, 35, and 70° peak
- Differential One-way Ranging Tones (coherent w/downlink carrier):
 - X-Band 880F1: 19.2 MHz
 - Ka-Band 3360F1: 19.2 MHz and 76.8 MHz

General

- Mass: 7.0 lbs (3.2 kg) maximum
- Input Supply Voltage: 22 to 36 VDC, or ±11 to ±18 VDC
- Input Supply Power:
 - Receiver Only: 12.5 W nominal
 - Receiver + X-Band Exciter: 15.8 W nominal
 - Receiver + X and Ka-Band Exciters: 19.5 W nominal
- Envelope Size: 7.13”L x 6.55”W x 4.50”H
- External Synch Frequency: 125 kHz nominal
- Radiation Total Dose: 50 krad (Si) (part level), 100 krad optional
- Operating Temperature: -40 to +60° C

GENERAL DYNAMICS
Mission Systems

Joseph Verderame • Manager, Business Development • 480.586.9973 • joseph.verderame@gd-ms.com • gdmissionsystems.com/space

©2015 General Dynamics. All rights reserved. General Dynamics reserves the right to make changes in its products and specifications at anytime and without notice. All trademarks indicated as such herein are trademarks of General Dynamics. All other product and service names are the property of their respective owners. © Reg. U.S. Pat. and Tm. Off.

D-SDST-02-1015